

Fuel Pressure Regulator Mini 2



- ▶ 5 to 10 bar
- ▶ 30 to 400 l/h reflow
- Adjusted at 105 l/h
- Aluminum housing
- All versions Methanol compatible

Fuel pressure regulators are used to maintain constant fuel pressure at the injection valves. We offer this regulator for gasoline as well as for methanol applications.

The main benefit of this regulator includes a higher pressure range and a higher return flow rate in comparison to the production type regulators.

Application

Pressure range	See ordering information
Reflow quantity	30 to 400 l/h
Fuel compatibility	Gasoline, E85, M100
Operating temperature	-40 to 120°C
Storage temperature	-40 to 100°C
Max. vibration	<600 m/s² at 5 to 250 Hz
Valve leakage	Q _{teck} [cm³/min] ≤ 9 (pneu- matic)
	at p [kPa] = 0.8 x P _{nom}

Technical Specifications

Variations

Please see Ordering Information

Mechanical Data

Diameter	38.1+0.1-0.2 mm
Weight	Ca. 61 g
Mounting	Fastening with a clip

Connectors and Wires

Connector supply	Diam. 25 mm, O-ring 25x2.5
Connector reflow	Diam. 9.1 mm, O-ring 5x2.5

Installation Notes

Never run the regulator without the integrated filter.

Please oil O-rings lightly with clean and silicone free engine oil before you install the regulator.

Please make a leak test after you have installed the regulator.

When the pressure regulator is removed and will be reused, the O-rings must be tested for fractures.

Operation of the pressure regulator with a medium other than gasoline is not allowed.


Using the FPR Adaptor light F02U.V02.248-01, you can rebuild the regulator an inline type.

This pressure regulator is not designed for in-tank mounting.

Ordering Information

Fuel Pressure Regulator Mini 2 Pressure Range 5.0 bar Order number F02U.V02.166-01
Fuel Pressure Regulator Mini 2 Pressure Range 6.0 bar Order number F02U.V02.168-01
Fuel Pressure Regulator Mini 2 Pressure Range 7.0 bar Order number F02U.V02.170-01
Fuel Pressure Regulator Mini 2 Pressure Range 8.0 bar Order number F02U.V02.171-01
Fuel Pressure Regulator Mini 2 Pressure Range 10.0 bar Order number F02U.V02.172-01
FPR Adaptor light Order number F02U.V02.248-01

Dimensions



Complete dimensions on offer drawing at www.bosch-motorsport.com

Represented by:

Europe: Bosch Engineering GmbH Motorsport Robert-Bosch-Allee 1 74232 Abstatt Germany Tel.: +49 7062 911 9101 Fax: +49 7062 911 79104 motorsport@bosch.com www.bosch-motorsport.de

North America: Bosch Engineering North America Motorsport 38000 Hills Tech Drive Farmington Hills, MI 48331-3417 United States of America TeL: +1 248 876 2977 Fax: +1 248 876 7373 motorsport@hosch.com motorsport@bosch.com www.bosch-motorsport.com

Asia-Pacific: Bosch Engineering Japan K.K. Motorsport 18F Queen's Tower C, 2-3-5 Minato Mirai Nishi-ku, Yokohama-shi Kanagawa 220-6218 Japan TeL: +81 45 650 5610 Fax: +81 45 650 5611 www.bosch-motorsport.jp

Australia, New Zealand and South Africa: Robert Bosch Pty. Ltd Motorsport 1555 Centre Road Clayton, Victoria, 3168 Australia Tel.: +61 (3) 9541 3901 motor.sport@au.bosch.com

 \circledast Bosch Engineering GmbH 2020 | Data subject to change without notice 50028811 | en, V, 26. Nov 2020