

Breakout Box BOB PBX 90



- ► Compact, lightweight housing in low-profile design with high-density packaging
- ► Robust 4 mm standard jacks for measuring leads
- ► Signal integrity of high-speed data links ensured by product-specific version
- Standard configurations and fully customized versions available
- ► No more lost jumpers due to patented 90° rotatable connectors

The Breakout Box BOB enables the operator to perform measurements and modify connections during operation. The jumpers allow to individually open or close each single connection without removing the jumper. Jacks provide access to all signals for measurement purposes. The box is essential for development and test environments in the lab and vehicle. This version was especially developed for use with PowerBox PBX 90.

Technical Specifications

Mechanical Data

Size 2	255 x 220 x 45 mm
--------	-------------------

Weight	2,400 g
4 mm standard jacks for meas- uring leads	68
Ethernet connectors	4
Ethernet wire	2 x inclusive

Connectors and Wires

Wire length L	2 x 60 cm

Ordering Information

Breakout Box BOB PBX 90
Order number F02U.V02.292-01

Represented by:

Europe: Bosch Engineering GmbH Motorsport Robert-Bosch-Allee 1 74232 Abstatt Germany Tel.: +49 7062 911 9101

Germany Tel.: +49 7062 911 9101 Fax: +49 7062 911 79104 motorsport@bosch.com www.bosch-motorsport.de

North America:

Bosch Engineering North America Motorsport 38000 Hills Tech Drive Farmington Hills, MI 48331-3417 United States of America Tel: +1 248 876 2977 Fax: +1 248 876 7373 motorsport@bosch.com www.bosch-motorsport.com

Asia-Pacific:

Bosch Engineering Japan K.K. Motorsport 18F Queen's Tower C, 2:3-5 Minato Mirai Nishi-ku, Yokohama-shi Kanagawa 220-6218 Japan Tel.: +81 45 650 5610

Japan Tel.: +81 45 650 5610 Fax: +81 45 650 5611 www.bosch-motorsport.jp

Australia, New Zealand and South

Africa: Robert Bosch Pty. Ltd Motorsport 1555 Centre Road Clayton, Victoria, 3168 Australia Tel.: +61 (3) 9541 3901 motor.sport@au.bosch.com