

Pressure Sensor Combined PST 1/ PST 3



- ▶ Pressure: 0.1 to 1.15 bar or 0.2 to 3 bar
- ▶ Temperature: -40 to 150°C or -40 to 140°C
- ▶ Power supply: 5 V
- ▶ Weight: 24 g

This sensor is designed to measure absolute air pressure, especially the air box pressure of gasoline or Diesel engines plus temperature. An integrated circuit combines a piezo-resistive sensor element and electronic systems for signal-amplification and temperature-compensation. The output of the sensor is an analog, ratio metric signal. Two different pressure ranges are available (0.1 to 1.15 bar or 0.2 to 3 bar).

Application

Application 1	0.1 to 1.15 bar or 0.2 to 3 bar (a)
Application 2	-40 to 130°C
Reference	Absolute
Max. pressure	5 bar
Operating temp. range	-40 to 130°C
Media temp. range	-40 to 130°C
Storage temp. range	0 to 40°C
Max. vibration	According to ISO 16750-3

Technical Specifications

Variations

	PST 1 (0.1 to 1.15 bar)	PST 3 (0.2 to 3 bar)
Tolerance (FS) at $U_s = 5\text{ V}$	$\pm 0.016\text{ bar}$	$\pm 0.030\text{ bar}$
Tolerance (FS)	$\pm 1.52\%$	$\pm 1.07\%$
Sensitivity	4,048 mV/bar	1,518 mV/bar
Offset	-4.76 mV	96.43 mV

Mechanical Data

Mounting	M6
Fitting	12.05 \pm 0.8 mm
Weight w/o wire	24 g
Sealing	O-ring 7.59 x 2.62 mm

Electrical Data

Power supply U_s	4.75 to 5.25 V
Max. power supply	16 V
Full scale output U_A at 5 V	0.4 to 4.65 V
Current I_s	9 mA

Characteristic 1


Response time T10/90	1 ms
Compensated range	10 to 85°C
Tolerance (FS) at $U_s = 5\text{ V}$	Please see variations
Tolerance (FS)	Please see variations
Sensitivity	Please see variations
Offset	Please see variations

Characteristic 2


T [°C]	R [Ohm]
-40	45,303
-30	26,108
-20	15,458
-10	9,395
0	5,895
10	3,791
20	2,499
25	2,056

30	1,706
40	1,174
50	833.8
60	595.4
70	435.6
80	322.5
90	243.1
100	186.6
110	144.2
120	112.7
130	89.28


Tolerance 0.1 to 1.15 bar



Tolerance 0.2 to 3 bar



Expansion of Tolerance



Connectors and Wires

Connector	Bosch Compact
Mating connector	D261.205.360-01
Pin 1	Ground
Pin 2	Temperature Signal
Pin 3	Power Supply
Pin 4	Pressure Signal

Various motorsport and automotive connectors are available on request.

Installation Notes

The PST 1/PST 3 is designed for engines using ROZ95, ROZ98, M15, E22 and Diesel.

The sensor can be connected directly to most control units.


To avoid noise, an ECU-input circuit with a RC-low pass filter (tau = 2 ms) is recommended.

Use engine oil (5W40) as O-Ring grease (no silicone based grease).

Avoid miss-pinning (max. 5 minutes at I = 0.3 A).

Please find further application hints in the offer drawing and free download of the sensor configuration file (*.sdf) for the Bosch Data Logging System at our homepage.

To avoid damage caused by condensate the maximum mounting position from vertical is +60°.



Safety Note


The sensor is not intended to be used for safety related applications without appropriate measures for signal validation in the application system.

Ordering Information

Pressure Sensor Combined PST 1
0.1 to 1.15 bar
Order number **0261.230.333**

Pressure Sensor Combined PST 3
0.2 to 3 bar
Order number **0261.230.280**

Dimensions



Represented by:

Europe:
Bosch Engineering GmbH
Motorsport
Robert-Bosch-Allee 1
74232 Abstatt
Germany
Tel.: +49 7062 911 9101
Fax: +49 7062 911 79104
motorsport@bosch.com
www.bosch-motorsport.de

North America:
Bosch Engineering North America
Motorsport
38000 Hills Tech Drive
Farmington Hills, MI 48331-3417
United States of America
Tel.: +1 248 876 2977
Fax: +1 248 876 7373
motorsport@bosch.com
www.bosch-motorsport.com

Asia-Pacific:
Bosch Engineering Japan K.K.
Motorsport
18F Queen's Tower C, 2-3-5 Minato
Mirai Nishi-ku, Yokohama-shi
Kanagawa 220-6218
Japan
Tel.: +81 45 650 5610
Fax: +81 45 650 5611
www.bosch-motorsport.jp

Australia, New Zealand and South Africa:
Robert Bosch Pty. Ltd
Motorsport
1555 Centre Road
Clayton, Victoria, 3168
Australia
Tel.: +61 (3) 9541 3901
motor.sport@au.bosch.com